

ROOFS



RESISTOBOARD SEMI-RIGID PROTECTION BOARD

is composed of a mineral fortified asphaltic core formed between two saturated fibreglass felts.

RESISTOBOARD is designed to be used as a substrate material in low-slope roofing or protection boards for waterproofing. It can be installed over wood, rigid insulation or as a recover sheet over an existing roof surface, which is to be re-roofed.

RESISTOBOARD is also used as a protective board with waterproofing foundation systems



RESISTOBOARD

SEMI-RIGID PROTECTION BOARD



- Compatible with most bitumen and built-up roofing systems
- Easy to handle and install
- Mold resistant
- Puncture resistant
- Durable
- Can be cut easily with a knife



**RESISTOBOARD
SEMI-RIGID PROTECTION BOARD**

RESISTOBOARD

**SEMI-RIGID
PROTECTION BOARD**

UPC Code: 1/8" x 4' x 5' : 6 23680 08420 9
1/4" x 4' x 5' : n/a

Product code	Dimensions	Approximate surface covered					
		per board		per board		per pallet	
		ft ²	m ²	ft ²	m ²	ft ²	m ²
08420	1/8" x 4' x 5' 3.2 mm x 1.22 m x 1.52 m	20	1.86	20	1.86	1,000	93
08421	1/4" x 4' x 5' 6.4 mm x 1.22 m x 1.52 m	20	1.86	20	1.86	1,200	111.6

Units per box: 1

Box per pallet: 1/8" x 4' x 5' : 50
1/4" x 4' x 5' : 60

Weight (±) per pallet: 1/8" x 4' x 5' : 908 lbs / 412 kg
1/4" x 4' x 5' : 2,262 lbs / 1,026 kg

RECOMMENDED USES

- Substrate material in roofing systems or asphalt shingles
- Protective board with any waterproofing foundation system

REQUIRED PRODUCT:

25 mm (1 in) round top nails

PRINTED IN CANADA • AR058-032008



CUSTOMER SERVICE

1 877 478.8408

www.resisto.ca