

ROOFS FOUNDATION

VARIOUS WATERPROOFING



RESISTO EXTERIOR PRIMER

is a synthetic polymer-based cold sealing compound containing natural resins and solvent.

Use it to prime and prepare exterior concrete, metal, wood and plywood surfaces to enhance the adherence of RESISTO self-adhesive membranes and waterproofing tape.

CPU Code:	910 ml:	6 23680 65751 9
	3.78 L:	6 23680 65755 7
	18.9 L:	6 23680 65745 8

Product code	Dimensions	Approximate surface covered					
		per can		per box		per pallet	
		ft ²	m ²	ft ²	m ²	ft ²	m ²
65751	910 ml	55	5	495	45	26,730	2,430
65755	3.78 L	208	19	416	38	31,200	2,850
65745	18.9 L	1,040	94	1,040	94	37,440	3,384

Units per box:	910 ml:	9
	3.78 L:	2
	18.9 L:	1
Boîtes par palette:	910 ml:	54
	3.78 L:	75
	18.9 L:	36
Weight (±) per pallet:	910 ml:	1,071 lb/486 kg
	3.78 L:	1,300 lb/590 kg
	18.9 L:	1,500 lb/680 kg

APPLICATION CONDITIONS

- Minimum application temperature: -10 °C (14 °F)
- Mix before and during application.
- Apply to clean, dry surfaces using a brush, roller or Airless sprayer.
- **Note:** Clean tools with petroleum solvents (petroleum spirits, Xylene, etc.)
- Let dry before installing the membrane.
- Drying time varies from ½ to 3 hours, depending on ambient temperature and amount applied.
- Dry when sticky to the touch but not messy.
- For best results, install the membrane or waterproofing tape as soon as the primer is dry.

STORAGE

Storage temperature: maximum 40 °C (104 °F)
Shelf life: 5 years in well-sealed original container when stored in a cool, well-ventilated area. **Note:** Seal container well after use.
N.B. REGULATED PRODUCT (see Material Safety Data Sheet)

EXTERIOR PRIMER



- Very flammable
- Resistant to water, alcohol and most saline, alkaline and dilute acid solutions
- Not resistant to oils, hydrocarbons or solvents



CUSTOMER SERVICE
1 877 478.8408
www.resisto.ca