

ROOFS

VARIOUS WATERPROOFING



RESISTO ANTICORROSION SEALANT

is a thick, homogeneous, SBS modified bitumen-based sealant containing reflective aluminium pigments and solvents.

Use it to restore and protect metal surfaces such as roofs, campers, mobile homes, farm buildings, reservoirs, water ducts, etc.

ANTICORROSION SEALANT



CPU Code: 3 L: 6 23680 65793 9
 18 L: 6 23680 65799 1

Product code	Dimensions	Approximate surface covered					
		per can		per box		per pallet	
		ft ²	m ²	ft ²	m ²	ft ²	m ²
65793	3 l	Coverage can vary between 20 to 40 ft ² /L (2 to 4 m ² /L)					
65799	18 l						

Units per box: 3 L: 2
 18 L: 1

Box per pallet: 3 L: 75
 18 L: 36

Weight (±) per pallet: 3 L: 1,405 lb/638 kg
 18 L: 2,436 lb/1 105 kg

- May be exposed to UV radiation
- May be used on conventional asphalt roofing and painted surfaces
- Should not be painted

APPLICATION CONDITIONS

- Minimum application temperature: 0 °C (32 °F)
- Mix before and during application; do not use an automatic mixer.
- Clean and dry surface before applying.
- Repair any holes and cracks with RESISTO ALL-PURPOSE ALUMINIUM WATERPROOFING MEMBRANE.
- Apply ANTICORROSION SEALANT using a brush, roller or Airless sprayer.
- **Note:** Clean tools with petroleum solvents (petroleum spirits, Xylene, etc.)
- Dries in approximately 24 hours.
- If a second coat is required, only apply once the first coat is completely dry. For a more aesthetic finish, the second layer must be thin therefore diluted at a rate of 25% solvent.

STORAGE

Storage temperature: maximum 40 °C (104 °F)
Shelf life: 5 years in well-sealed original container when stored in a cool, well-ventilated area.
Note: Seal container well after use.
N.B. REGULATED PRODUCT (see Material Safety Data Sheet)



IMPORTÉ AU CANADA • AK065-032008



CUSTOMER SERVICE
1 877 478.8408
www.resisto.ca