

RESISTO

WINTER PRO PLASTIC CEMENT

MASTIC



A versatile mastic formulation suitable for low temperature application. It is used to seal flashings, vents, upstands and other roof components, as well as to repair various joints, holes and cracks.

- Application on dry or wet surfaces, even in cold weather
- Excellent resistance to temperature variations
- Use without primer

PRODUCT PURPOSE

Application	Waterproofing complement	
Building Part	Roofing	Foundations
	Walls	Other
Substrates	Wood	Asphalt shingles
	Concrete	Metal

PRODUCT CHARACTERISTICS

Installation Method	Trowel
Operating Temperature	-40 °C to 80 °C (-40 °F to 176 °F)

PACKAGING

Code	Containers	Quantity per Pallet
53016	20 kg (44 lb)	36


PROPERTIES

Properties	WINTER PRO PLASTIC CEMENT
Color	Black
Solids by Weight	86%
Flow	None at these temperatures

All values are nominal)

WINTER PRO PLASTIC CEMENT

INSTALLATION

Storage	Two years in its original closed packaging, in a cool, well-ventilated area. Store in a cool, dry place up to 40 ° C (104 ° F). The product can withstand freezing.
Minimum Application Temperature	-10 ° C (14 ° F). The product must be at a minimum temperature of 10 ° C (50 ° F) before application.
Tools Required	 Trowel
Surface Preparation	The substrate must be clean and free of dust, grease or other contaminants.
Installation	Apply with a trowel.
Drying time	Between 4 and 24 hours, depending on ambient temperature and the amount applied.
Recommendations/ Limitations	Do not apply strips greater than 1 cm (1/2 in) in width. It is not recommended to use a product containing bitumen directly on softwood boards or on flexible polyvinyl chloride.
Warnings	Keep out of the reach of children. Properly close the container after each use. Keep out of the sun and away from ignition sources. During use, keep away from ignition sources. No smoking. After application, keep away from flames until solvent has evaporated. Do not pour residues in drains.

