

RESISTO

REGULAR PLASTIC CEMENT

MASTIC



An economic mastic used to seal flashings, vents, upstands and other roof components, as well as to repair various joints, holes and cracks.

- Economic
- Excellent resistance to temperature variations
- Use without primer

PRODUCT PURPOSE

Application	Waterproofing	
Building Part	Roofing	Foundations
	Walls	Other
Substrates	Wood	Asphalt shingles
	Concrete	Metal

PRODUCT CHARACTERISTICS

Installation Method	Extruder	Trowel
Operating Temperature	-40 °C to 80 °C (-40 °F to 176 °F)	

PACKAGING

Code	Containers	Quantity per Pallet
53003	300 ml (10 oz)	1200
53004	4 kg (2.2 lb)	150
53006	10 kg (22 lb)	48
53005	20 kg (44 lb)	36



PROPERTIES

Properties	REGULAR PLASTIC CEMENT
Color	Black
Solids by Weight	86%
Flow	None at these temperatures

(All values are nominal)

REGULAR PLASTIC CEMENT

INSTALLATION

Storage	Two years in its original closed packaging, in a cool, well-ventilated area. Store in a cool, dry place up to 40 ° C. The product can withstand freezing.
Minimum Application Temperature	0 °C (32 °F).
Tools Required	 Extruder  Trowel
Surface Preparation	The substrate must be clean and free of dust, grease or other contaminants.
Installation	Apply with a trowel or an extruder.
Drying time	Between 4 and 24 hours, depending on ambient temperature and the amount applied.
Recommendations/ Limitations	Do not apply strips greater than 1 cm (1/2 in) in width. It is not recommended to use a product containing bitumen directly on softwood boards or on flexible polyvinyl chloride.
Warnings	Keep out of the reach of children. Properly close the container after each use. Keep out of the sun and away from ignition sources. During use, keep away from ignition sources. No smoking. After application, keep away from flames until solvent has evaporated. Do not pour residues in drains.

