

ASPHALT RESTORER 2 AND 5 YEARS

PROTECTION

Water-based, acrylic coating (coal tar-free) used to prevent cracks and deterioration caused by wear, freezing, oil and gas spills, salt sand and rain.

- Has a very black and shiny finish
- No unpleasant odor
- Easy and fast application

PRODUCT PURPOSE

Application	Asphalt surface protection
Substrate	Asphalt


PRODUCT CHARACTERISTICS

Installation Method	Roller
---------------------	--------

PACKAGING

Code	Containers	Indicative Covering	Quantity per Pallet
38139	15 l (3.9 US gal)	30 m ² to 135 m ² (325 to 1450 ft ²)	36
38135			

INSTALLATION

Storage	3 years in the original container. Store in a cool, dry place, between 10 ° C (50 ° F) and 40 ° C (104 ° F). Keep away from frost.
Min. Application Temperature	10 ° C (50 ° F)
Tools Required	 Roller
Surface Preparation	The substrate must be clean, dry and free of dust, grease or other contaminants.
Installation Prerequisite	Before hand repair the surface with RESISTOSEAL asphalt maintenance range of products.
Installation	<ol style="list-style-type: none"> 1. To clean the surface, spray water, then using a brush remove any dirt or dust. 2. Mix thoroughly until smooth. 3. Start by the highest part of the surface to be covered. 4. Pour the ACRYLIC ASPHALT RESTORER in ribbon shapes and apply the product with a roller, taking care not to leave any excess product on the surface.
Drying time	24 hours
Cleaning	Clean damp tools with water. When dry, clean with solvents such as mineral spirits, paint thinner or xylene.
Tricks / Tips	For best results, do not apply the product in direct sunlight. In very hot weather, water the area first, before application, ensure that there is no standing water on the surface.
Recommendations/ Limitations	Avoid applying the product if there is a risk of rain, high humidity or frost within 24 hours of application. The asphalt surface must cure for a minimum of 15 days before the application of the ASPHALT RESTORER. Adhesion may be reduced if the product is applied over a coal tar-based sealer.

