



## CRACK FILLER FOR ASPHALT SURFACES

TECHNICAL DATA SHEET  
100222RCAN3E  
(supersedes -090707RCAN1E)

### DESCRIPTION

The **RESISTOSEAL CRACK FILLER** for asphalt surfaces is designed to repair small cracks and joints into asphalt pavement.

The **RESISTOSEAL CRACK FILLER** protects against water infiltration into asphalt pavement breakdown caused from wear, rain and freezing temperatures.

### APPLICATION CONDITIONS

- Application temperature: 10 °C (50 °F) or more. However, product can be applied at lower temperatures if conditioned at a temperature of 10 °C or more.
- Surface must be clean and dry.

### PACKAGING & COVERAGE

- 300 ml tubes
- Average coverage: A bead of 1/4 in. (6 mm) covers approximately 29 linear feet (9 meters).

### GENERAL INSTRUCTIONS

- Clean surface using water, let dry completely.
- Fill deep cracks using sand up to 3/8 in. (10 mm) of the top surface.
- Apply **RESISTOSEAL CRACK FILLER** using a regular caulking gun and let dry.

### LIMITATIONS

- Designed for cracks up to 3/8 in. (10 mm) wide. For wider cracks, use **RESISTOSEAL LEVELING PATCH** or **ASPHALT REPAIR**.
- Allow product to cure completely before applying **RESISTOSEAL DRIVEWAY SEALER**.

For further information, consult the Material Safety Data Sheet.

### STORAGE

- Maximum storage temperature: 40 °C (104 °F).
- Can support storage temperatures below 0°C (32 °F).
- Storage conditions: 2 years in its original packaging.  
Store in a cool, well-ventilated place.

