



OIL SPOT PRIMER



SOLUTIONS ÉTANCHÉITÉ
WATERPROOFING SOLUTIONS

www.resisto.ca

TECHNICAL DATA SHEET
101101RCAN1E
(supersedes ---)

DESCRIPTION

The **RESISTOSEAL OIL SPOT PRIMER** is a polymer emulsion that enhances the adhesive strength of **RESISTOSEAL ASPHALT DRIVEWAY SEALERS** onto asphalt surfaces affected by oil sediments.

APPLICATION CONDITIONS

- Application temperature: 10 °C (50 °F) or more.
- Surface must be sound and clean

PACKAGING & COVERAGE

- Bottle of 946 ml

GENERAL INSTRUCTIONS

- Remove all loose dirt and debris.
- Clean the surface using **RESISTOSEAL CLEANER & DEGREASER**.
- Apply a thin coat of **RESISTOSEAL OIL SPOT PRIMER** to the surface to be treated, and let dry.
- Apply one of the **RESISTOSEAL DRIVEWAY SEALER** to protect the surface.

LIMITATIONS

- If the asphalt surface is softened by oil or gasoline, it is suggested to remove the damaged area and to repair it with **RESISTOSEAL ASPHALT REPAIR**.
- Keep from freezing.

For further information, consult the Material Safety Data Sheet.

STORAGE

- Minimal storage temperature: 10 °C (50 °F)
Maximum storage temperature: 40 °C (104 °F).
- Shelf life: 3 years in original unopened pail.

