



ASPHALT REPAIR

TECHNICAL DATA SHEET
100423RCAN1E
(supersedes ---)

DESCRIPTION

The **RESISTOSEAL ASPHALT REPAIR** is composed of a ready to use mixture of adherent aggregates. It forms a solid bond with all firm surfaces, wet or dry.

APPLICATION CONDITIONS

- Can be applied at any temperature onto asphalt surfaces, either for residential or commercial purpose.

PACKAGING & COVERAGE

- 15 kg pail
- 20 kg bag

A 20 kg bag covers around 5.7 sq. ft (0.53 m²) for a depth of 1 in. (25 mm).

GENERAL INSTRUCTIONS

- The **RESISTOSEAL ASPHALT REPAIR** is designed to fill potholes and cracks of 3/4 in. (20 mm) and more.
- Surface must be sound and clean. Remove crumbled asphalt or any loose material and remove ponding water.
- Slightly overfill holes and compact using a shovel or a tamper.
- If needed, lightly dust the surface using sand to reduce its adhesion while curing.
- Let surface opened to traffic immediately to accelerate the curing time.

LIMITATIONS

- Allow the **RESISTOSEAL ASPHALT REPAIR** to cure completely (firm and dry) before applying a **RESISTOSEAL DRIVEWAY SEALER**.
- The **RESISTOSEAL ASPHALT REPAIR** must be pressed beside solid asphalt to ensure proper compaction and best performance.

For further information, consult the Material Safety Data Sheet.

STORAGE

- Can be stored at temperature below 0 °C (32 °F).
- Storage conditions: 2 years in its original packaging.

