



LIQUID CRACK FILLER

For asphalt surfaces



SOLUTIONS ÉTANCHÉITÉ
WATERPROOFING SOLUTIONS

www.resisto.ca

TECHNICAL DATA SHEET

100222RCAN2E

(supersedes -090903RCAN1E)

DESCRIPTION

The **RESISTOSEAL LIQUID CRACK FILLER** for asphalt surfaces is designed to repair small cracks and joints into asphalt pavement.

The **RESISTOSEAL LIQUID CRACK FILLER** protects against water infiltration into asphalt pavement breakdown caused from wear, rain and freezing temperatures.

APPLICATION CONDITIONS

- Application temperature: 10 °C (50 °F) and above.
- Surface must be clean and dry.

PACKAGING & COVERAGE

- 946 ml bottle
- 3.78 L bottle

GENERAL INSTRUCTIONS

- Surface must be free of dust, dirt and debris, and must be dry.
- Apply **RESISTOSEAL LIQUID CRACK FILLER** directly onto cracks and let dry.
- Repeat application if needed.

LIMITATIONS

- Designed for cracks up to 1/4 in. (6 mm) wide. For wider cracks, use **RESISTOSEAL RUBBERISED CRACK FILLER, LEVELING PATCH** or **ASPHALT REPAIR**.
- Do not apply product when rain or freezing temperature is expected within the next 24 hours after installation.
- Allow product to cure completely (firm and dry) before applying **RESISTOSEAL DRIVEWAY SEALER**.

For further information, consult the Material Safety Data Sheet.

STORAGE

- Maximum storage temperature: 38 °C (100 °F).
- Keep from freezing!
- Storage conditions: 2 years in its original packaging.

