



CLEANER AND DEGREASER

TECHNICAL DATA SHEET
101028RCAN1E
(supersedes ---)

DESCRIPTION

The **RESISTO SEAL CLEANER AND DEGREASER** is used to dissolve and clean oil and grease spots from asphalt driveways.

APPLICATION CONDITIONS

- Application temperature: 10 °C (50 °F) or more.
- Surface must be sound and clean

PACKAGING & COVERAGE

- Bottle of 946 ml

GENERAL INSTRUCTIONS

- Remove all loose dirt and debris.
- Pour a liberal amount of **CLEANER AND DEGREASER** on the surface to be treated.
- Vigorously scrub area with a very stiff broom or brush.
- While the surface is still wet, rinse thoroughly with a hose. Repeat this step until there are no bubbles in the rinse water.

Notes: Prior to install one of the **RESISTO SEAL DRIVEWAY SEALERS**, apply **RESISTO SEAL OIL SPOT PRIMER** onto the surfaces to be treated.

LIMITATIONS

- If the asphalt surface is softened by oil or gasoline, it is suggested to remove the damaged area and to repair it with **RESISTO SEAL ASPHALT REPAIR**.
- Keep from freezing.

For further information, consult the Material Safety Data Sheet.

STORAGE

- Minimal storage temperature: 10 °C (50 °F)
Keep from freezing!
- Maximum storage temperature: 40 °C (104 °F).
- Shelf live: 12 months in original unopened pail.

